


IN-LINE RED MINI CHECK VALVE - SPRING LOADED

In-Line Mini Check Valve housing is red polypropylene with 5/16" barbed fittings at both ends. Internal o-ring is ethylene-propylene and the spring is 316 stainless steel. The check valve opening pressure is 6" of water.

ITEM	QTY.	MODEL NO.	FULL			
		IN-LINE MINI CHECK VALVE	 ACORN VAC, INC 13818 OAKS AVENUE, CHINO, CA 91710 (800) 591-9920 - FAX (909) 902-5041			
JOB						
LOCATION						
ARCH.			DATE	REVISION	DRN. BY	DWG. NO.
M.E. \PUBLIC\SUBMITTAL DRAWINGS			11/21/07		JMT	2803-007-000

DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE. WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA. THIS PRINT IS CONFIDENTIAL AND IS LOANED FOR MUTUAL ASSISTANCE. IT IS NOT TO BE FORWARDED TO OTHER PARTIES NOR REPRINTED IN ANY FORM WITHOUT OUR WRITTEN PERMISSION.